

SHOPRIDER®

Compact Scooters



User Manual

Table of Contents

INTRODUCTION	3
FEATURE GUIDE (FIG. 1-4)	3
SAFETY ADVICE	5
EMI Warning	6
ADJUSTMENTS	7
Tiller Angle Adjustment (Fig. 5).....	7
Folding the Tiller (Fig. 6).....	7
Seat Slide & Swivel Adjustment (Fig. 7).....	7
Seat Removal (Fig. 8).....	7
Seat Height Adjustment (Fig. 8).....	7
Armrest Width Adjustments (Fig. 9).....	8
Armrest Angle Adjustment (Fig. 10).....	8
Scooter Length Adjustment (Fig. 11).....	8
Scooter Width Adjustment (Fig. 12).....	8
SCOOTER TILLER CONTROLS (FIG. 13)	9
Speed Controls.....	9
Battery Level Indicator/Gauge.....	9
Horn.....	9
Thumb Lever Controls.....	9
On/Off Key Switch.....	9
Electromagnetic Brake.....	9
FREE WHEEL OPERATION (FIG. 14)	10
Anti-tip wheels.....	10
STARTING TO DRIVE YOUR SCOOTER	10
Getting Started.....	10
Starting Scooter Movement.....	10
Steering.....	11
Reversing.....	11
Dismounting.....	11
EXTRA GUIDELINES IN THE CONTROL OF YOUR SCOOTER	11
Ramps.....	11
Grass and Gravel.....	11
TRANSPORT / STORAGE	12
Dismantling.....	13
BATTERIES AND BATTERY CHARGER	13
Battery Charger.....	13
Charging.....	13
MAINTENANCE	14
Lubrication.....	14
Wheels and Tires.....	14
TROUBLE SHOOTING GUIDE	14
Circuit Breaker.....	14
Check List.....	14
TECHNICAL SPECIFICATIONS	15
QUARTERLY INSPECTION	16
WARRANTY	17
DISCLAIMER	17

INTRODUCTION

Congratulations on your purchase of the Shoprider® scooter. This scooter incorporates the latest innovative designs patented and only available on a Shoprider® scooter. This scooter can be used in confined spaces both indoors and out. Direct drive transaxles and electromagnetic brakes give a safe and efficient ride. This Shoprider® scooter is designed for persons with limited mobility.

Please ensure that you read this manual carefully, it is important for your safety that you understand the guidelines and instructions given.

FEATURE GUIDE (FIG. 1-4)

XtraLite 3 (Figure 1)

1. Tiller control head
2. Detachable seat with fold down back
3. Detachable basket
4. Detachable battery
5. Tiller release knob
6. Carrying stay rod
7. Seat height adjustment
8. Puncture proof tires



Figure 1

XtraLite 4 (Figure 2)

1. Tiller control head
2. Detachable seat with fold down back
3. Detachable basket
4. Detachable battery
5. Tiller angle adjustment
6. Seat height adjustment
7. Anti-Tip wheels
8. Puncture proof tires



Figure 2

Scootie (Figure 3)

1. Tiller control head
2. Detachable seat with fold down back
3. Detachable basket
4. Detachable cover with integral battery pack
5. Tiller release knob
6. Carrying stay rod
7. Seat height adjustment
8. Anti-Tip wheels
9. Puncture proof tires



Figure 3

Sunrunner S (Figure 4)

1. Tiller control head
2. Detachable swivel seat with fold down back
3. Detachable basket
4. Detachable cover with integral battery pack
5. Tiller angle adjustment
6. Seat height adjustment
7. Puncture proof tires



Figure 4

SAFETY ADVICE

- Do not carry passengers.
- Do not exceed inclines over 8 degrees (14% grade).
- Do not turn on steep inclines.
- Do not turn suddenly at high speeds.
- Do not get on or off the scooter unless the brake is on and the scooter is switched off.
- Do not switch off the scooter while the scooter is moving.
- Do not drive the scooter where you can not safely or legally walk.
- Do not attempt to drive over curbs greater than 2 inches (5cm.) in height. Doing so could cause your scooter to turn over, causing injury or damage to the scooter. For curbs less than 2 inches, always approach them at an angle of 90 degrees and at a low speed.
- Do not drink or use a mobile phone when driving your scooter.
- Do not exceed the suggested user weight limit. Doing so, could cause personal injury and invalidate the warranty.
- Always keep your feet on the scooter when moving.
- Consult your doctor if there is any doubt about your ability to use a scooter safely.
- Always slow down and proceed carefully when traveling over rough or uneven ground.
- For individuals with balance problems practice getting on the scooter with assistance of a qualified healthcare professional.
- If equipped, DO NOT operate the scooter without anti-tip wheels installed.
- Do not use an escalator to move a scooter between floors. Serious injury could occur.
- Do not drive the scooter on an incline that has oil, water or ice film on it.
- Do not try to lift the scooter by its seat, tiller, rear chassis cover, or any removable parts. Any of these could cause injury to the user or damage to the scooter.
- Do not use parts or accessories that are not authorized by Shoprider® Mobility Products, Inc.
- Before sitting in or exiting the scooter, REMOVE the key from the ignition. This will insure the POWER is off and the scooter can not move under its own power.
- As a general precaution, always remove the key from the ignition while the scooter is not in use. This will prevent use by untrained and unauthorized persons.
- Do not connect any medical device to the scooter battery. This could cause failure of the device, the scooter and personal injury.
- Make sure the tiller is properly adjusted to the user or damage and injury could result.
- Shoprider® Mobility Products, Inc. does not recommend that scooter users be transported in a vehicle WHILE they are in the scooter...and will not be responsible for any injury or damage that might result.
- Do not use the scooter in the rain, near a shower or in a damp bathroom. Direct exposure to rain or dampness could cause the scooter to electrically malfunction and prematurely rust.
- For maximum battery life, make sure to fully charge batteries for 8 hours prior to usage.

EMI Warning

Shoprider® scooters may be susceptible to electromagnetic interference (EMI), which is a kind of interfering electromagnetic energy (EM) emitted from sources such as radio stations, TV stations, amateur radio (HAM) transmitters, two-way radio, and cellular phones. The interference (from radio wave sources) can cause the scooter to release its brakes, move by itself, or move in unintended directions. It can also permanently damage the scooter's control system. The sources of radiated EMI can be broadly classified into three types:

1. Hand-held portable transceivers (transmitters-receivers) with the antenna mounted directly on the transmitting unit. Examples include: citizens band (CB) radios, "walkie talkie", security, fire and police transceivers, cellular telephones, and other personal communication devices.

NOTE! Some cellular telephones and similar devices transmit signals while they are ON, even when not being used.

2. Medium-range mobile transceivers, such as those used in police cars, fire trucks, ambulances, and taxis. These usually have the antenna mounted on the outside of the vehicle.
3. Long-range transmitters and transceivers, such as commercial broadcast transmitters (radio and TV broadcast antenna towers) and amateur (HAM) radios.

NOTE! Other types of hand-held devices, such as cordless phones, laptop computers, AM/FM radios, TV sets, CD players, and cassette players, and small appliances, such as electric shavers and hair dryers, so far as we know, are not likely to cause problems to the scooter.

Scooter Electromagnetic Interference (EMI)

Because EM energy rapidly becomes more intense as one moves closer to the transmitting antenna (source), the EM fields from hand-held radio sources (transceivers) are of special concern. It is possible to unintentionally bring high levels of EM energy very close to the scooter's control system while using these devices. This can affect scooter movement and braking. Therefore, the warnings listed below are recommended to prevent possible interference with the control system of the scooter.

WARNINGS

1. Do not operate hand-held transceivers (transmitters-receivers), such as citizens band (CB) radios, or turn ON personal communication devices, such as cellular phones, while the scooter is turned ON.
2. Be aware of nearby transmitters, such as radio or TV stations, and try to avoid coming close to them.
3. If unintended movement or brake release occurs, turn the scooter OFF as soon as it is safe.
4. Be aware that adding accessories or components, or modifying the scooter may make it more susceptible to EMI.

NOTE! There is no easy way to evaluate the overall immunity of the scooter.

5. Report all incidents of unintended movement or braking to your Shoprider® dealer, and note whether there are sources of EMI nearby.

WARNING: Shoprider® Mobility Products, Inc. is not responsible for damage or injury incurred due to improper and unsafe use of our scooter.

ADJUSTMENTS

Tiller Angle Adjustment (For XtraLite 4 & Sunrunner S ONLY) (Fig. 5)

On the left hand side at the base of the tiller is a red lever. Push the lever in to release the pin and select the required tiller angle. Refit the pin into one of the five location holes.




Figure 5

Folding the Tiller (For XtraLite 3 & Scootie ONLY) (Fig. 6)

Fold down the tiller by loosening the hand knob located at the base of the tiller stem.



Figure 6

Seat Slide & Swivel Adjustment (For Sunrunner S ONLY) (Fig. 7)

Pulling up on the lever allows the seat position to be adjusted forward or backward. Release the lever and the seat will lock in that position. Under the right side of the seat there is a spring loaded red lever. Pulling up on the lever allows the seat to swivel, when released the seat will lock into one of 4 positions.



Figure 7

Seat Removal (Fig. 8)

Fold down the back of the seat. Remove the seat hand knob and locking pin that secures the seat adaptor. Lift the seat adaptor out of the seat post.

Seat Height Adjustment (Fig. 8)

Remove seat as described above. Loosen the lower hand knob. The seat height can be adjusted to 5 different settings by inserting the steel locking pin in the required hole. Retighten the lower hand knob and replace the seat.




Figure 8

Do not use the scooter without the arms being fitted.

Armrest Width Adjustments (Fig. 9)

On the underside of the seat there are two hand knobs, one on each side. Loosening the arm rest tightening knob allows the armrest width to be adjusted or arm rests to be removed.

Armrest Angle Adjustment (Fig. 10)

Flip up the armrests to allow access to the adjustment screw and lock nut, unscrew the lock nut and screw the bolt in or out to increase or decrease the angle. Re-tighten the lock-nut. Your scooter is dispatched from the factory with the armrests set parallel to the floor.

Scooter Length Adjustment (For Scootie & Sunrunner S) (Fig. 11)

The wheel base can be lengthened or shortened depending on its existing settings. The standard length of the scooter can be extended up to 3 inches. To adjust the wheelbase, remove the seat and the chassis cover complete with integral batteries. Remove the locking pin located at the front of the seat post (Fig. 8). Unscrew the red hand lever in front of the pin by turning counter-clockwise. Loosen the clips that secure the wires along the chassis. Slide the inner front section until the location holes become aligned. Insert the locking pin and tighten the red hand lever, insuring when fully secured, the lever is facing the seat post as shown in Fig. 11. Replace the chassis cover with the integral batteries then replace the seat.

Scooter Width Adjustment (For XtraLite 3) (Fig. 12)

Remove seat as described above. Remove rear basket. Remove U-shaped pins, adjust wheels to proper hole. Replace U-shaped pins.

Caution – Width of the wheels MUST be adjusted evenly on both sides to avoid injury.



Figure 9




Figure 10




Figure 11





Figure 12

SCOOTER TILLER CONTROLS (FIG. 13)

Speed Controls

The speed control allows you to set a speed between 1 (minimum) and 10 (maximum).

Battery Level Indicator/Gauge

The number of LED bars lit/where the needle sits, shows the amount of charge left in your batteries. The amount of charge will only show at its true level when the scooter is in drive.

Caution – Do not allow the LED bars/gauge needle to go out completely as complete discharge of the batteries could cause irreversible damage.

Horn

A yellow button at the rear of the tiller operates the horn.

Thumb Lever Controls

The left thumb lever controls the reverse and the right thumb lever controls the forward motion. The amount of pressure applied to each lever will determine the speed the scooter travels at. Release the lever and the scooter will slowly come to a stop and the electromagnetic brake will be applied.

On/Off Key Switch

Insert the key in the right side of the tiller. Turn the key and the LED bars will light up/the needle will move. For XtraLite 3 and XtraLite 4 make sure to turn on the batteries, and for XtraLite 3 turn on the scooter by the power button located next to the horn. There is a delay before the thumb lever control can be operated, while the controller is checking the circuits.

Electromagnetic Brake

The brake is automatically operated when the control levers are pressed or released. There is a slight delay when the scooter decelerates; this allows the scooter to come to a smooth stop.




Figure 13

FREE WHEEL OPERATION (FIG. 14)

The free wheel release lever (red handle) is located next to the right rear wheel (Fig. 14). To disengage the motor, lift up the lever (the scooter can now be pushed). To re-engage the motor push down on the lever.

***WARNING! Always re-engage the free wheeling device after use.
Failure to do so may result in injury.***

Anti-tip wheels

The anti-tip wheels are located at the rear of the scooter frame (Fig. 14). The scooter should not be used unless the anti-tipping wheels are in place.

Shoprider® Mobility Products, Inc. is not responsible for damage or injury incurred due to improper or misuse of the scooter.



Figure 14

STARTING TO DRIVE YOUR SCOOTER

Getting Started

- Select a level area with plenty of space.
- Mount the scooter, either by lifting the arm and sliding onto the seat or rotate the seat outwards and then rotate the seat back to face the tiller.
- Adjust the tiller and seat as previously described.

Starting Scooter Movement

- Ensure that you are seated in a comfortable position.
- Turn the key to the on position.
- Your speed setting should be on 1 or 2.
- Push your right hand thumb lever and the scooter will move forward slowly. The harder you press, the faster the scooter goes but will only reach the speed level that has been selected.
- Release the lever and the scooter will slowly come to a stop as the magnetic brake automatically engages.

Steering

Steering the scooter is light and easy. Ensure when starting off you give a wide clearance when turning so that the rear wheels clear any obstacle that you are passing. When steering through limited spaces such as a doorway or when turning around, turn the tiller handles where you want to go and apply power gently. The scooter will turn very tightly, but will still move with complete stability as long as the speed is not too high.

Reversing

Before reversing ensure that the area behind is free from any hazards or obstructions. Adjust your speed setting to a low setting before you reverse. Press the left thumb lever, and steer wide of all corners and obstacles.

Dismounting

Before dismounting ensure that the key is turned to the off position.

CAUTION: Please ensure that care is exercised when entering or leaving the scooter and that the tiller and foot rest is not used for support.

EXTRA GUIDELINES IN THE CONTROL OF YOUR SCOOTER

Ramps

The stability of your scooter is governed by several factors such as the seating position, the angle of the slope and your height and weight. When approaching an incline, do so directly and not at an angle and where ever possible avoid making turns. When going down a ramp or slope keep the speed settings to slow. This will ensure there is a safe controlled descent. When the finger levers are released the scooter will slowly stop.

Caution - Do not turn off the control key while the unit is in motion

Grass and Gravel

Please follow the guidelines given previously and your scooter will perform admirably over many surfaces. Avoid long grass, loose gravel and sand.


NOTE: You should not operate your scooter in wet weather or on wet surfaces. This may cause the motor to short out.

TRANSPORT / STORAGE

The scooters are designed to be dismantled into separate sections for transportation and storage. Your scooter can be dismantled into the following sections:

XtraLite 3 (Fig. 15)

- 1) Small Front Basket
- 2) Large Rear Basket
- 3) Seat
- 4) Seat Post & Fasteners
- 5) Battery Pack
- 6) Fold Down Frame



XtraLite 4 (Fig. 16)

- 1) Small Front Basket
- 2) Large Front Basket
- 3) Seat
- 4) Seat Post & Fasteners
- 5) Battery Pack
- 6) Fold Down Frame




Scootie (Fig. 17)

- 1) Basket
- 2) Seat
- 3) Seat Post & Fasteners
- 4) Rear Chassis
- 5) Front Chassis
- 6) Rear Shroud



Sunrunner S (Fig. 18)

- 1) Basket
- 2) Seat
- 3) Seat Post & Fasteners
- 4) Rear Chassis
- 5) Front Chassis
- 6) Rear Shroud



Dismantling

1. Remove baskets.
2. Fold down the back of the seat.
3. For Sunrunner S: pull up on the red lever under the seat and at the same time lift and twist the seat off.

For XtraLite 3; XtraLite 4; Scootie: unscrew the tightening bolt below the seat. Lift seat off.

For XtraLite 3 & XtraLite 4 ONLY.

1. Lower tiller toward the foot rest and connect the carrying rod (For XtraLite 3) to the proper location or connect the two Velcro straps (For XtraLite 4) to the handle bars.

For Scootie & Sunrunner S ONLY.

2. Remove the rear chassis cover/battery pack.
3. Remove the locking pin and separate the rear drive unit (Fig. 11).
4. Lower the tiller to its lowest level on the front chassis and connect the carrying rod (if the rear drive unit is NOT separated).

BATTERIES AND BATTERY CHARGER

The Shoprider® scooter is supplied with maintenance free, sealed lead acid batteries. Battery performance can be affected by temperature, terrain, condition of battery, the weight of the user, etc. The battery level indicator is only a guide and is most effective when the scooter is moving, only then is the true discharge level displayed.

- When the scooter stops the battery level indicator may indicate full.
- An active user can use up to 30% of battery capacity or more per day.
- Inactive users may only use 50% of battery capacity in a week.
- In both these instances the battery should be put on charge over night.

Battery Charger

Batteries supplied with your scooter are specially designed. All units require an automatic battery charger. XtraLite 3 and XtraLite 4 have built in charger ports on the side of the battery pack. The battery chargers are 2-amp transformer type off board.

Charging

To charge the batteries connect the plug lead into the battery-charging socket on the scooter/battery pack and the 2 or 3-prong plug into the wall socket and switch on. **FOR Scootie and Sunrunner S ONLY:** the battery charger has two lights. The red light when constant shows the battery charger is connected if the red light flashes; there is a break in the connection. A steady green light will show the unit is charging. When the light turns solid red again while still plugged into the charging port the unit is fully charged. ***DO NOT OVER CHARGE THE UNIT.***

FOR XTRALITE 3 & 4: Connect 3 prong round plug to their charging port, located on the side of the battery pack. The charger will show a solid green light when plugged in the all. Once plugged into the charging port a steady red light will indicate that the unit is charging. When the red light turns green while still connected to the charging port, the unit is fully charged. ***DO NOT OVER CHARGE THE UNIT.***

CAUTION: Always ensure that the charging lead is in good condition and has not been damaged or stretched.

MAINTENANCE

Lubrication

At six-month intervals you should lubricate the following parts with a light oil or similar lubricant:

- Seat pivot post.
- Seat release lever pinion.
- Wheel bearings.
- Axle of scooter.

CAUTION – DO NOT USE WD40 TO LUBRICATE PARTS!! DO NOT LUBRICATE TRANSAXLE/GEAR BOX!! In the event of any difficulties please consult your dealer.

Wheels and Tires

The wheels of your scooter might have split rims (except for the XtraLite 3 where the rim and tire are one molded piece together). To change the wheels remove the center bolt and slide the wheel off its axle. Ensure that when refitting the wheel the retaining bolt is fitted with a locking washer or the screw threads are treated with lock-tite or a similar adhesive.

TROUBLE SHOOTING GUIDE

Circuit Breaker

Your scooter is fitted with the latest in electronic controls that are programmed to protect the electrical system from abnormal overloads. Provided for extra protection is a circuit breaker. Should there be a situation where your scooter stops for no apparent reason, please check that the circuit breaker has not popped. **ON THE SCOOTIE AND SUNRUNNER S** the circuit breaker can be found under the rear chassis cover accessible through a port hole under the seat and can be reset by pressing the black button. **ON THE XTRALITE 3 AND XTRALITE 4** the circuit breaker is located on the side of the battery pack.

Check List

If your scooter fails to operate, please check the following:

- Unit is switched on.
- All plugs and connectors are clean and firmly connected.
- Battery level shows full charge.
- Freewheeling device is in the drive position.

If the free wheel device has been operated with the scooter switched on, then the scooter will not operate until the ignition key has been switched off and then on again.

Please consult your dealer if your scooter does not run after checking these points.

TECHNICAL SPECIFICATIONS

UNIT SPECIFICATIONS		XtraLite 3	XtraLite 4	Scoutie	Sunrunner S
Overall Dimensions: L ¹ x W x H	in (mm)	45 (1130) x 21 (520) x 37 (930)	41 (1040) x 20 (510) x 35 (890)	37-40 (930-1015) x 17 (430) x 34 (865)	43-46 (1090-1168) x 22 (560) x 35 (890)
Number, Size of Tires	Front	1 , 8"	2 , 7"	2 , 7"	2 , 8"
	Rear	2 , 8"	2 , 8"	2 , 8"	2 , 8"
Suggested User Weight (on the level road)	lb (kg)	Max. 220 (100)	Max. 220 (100)	Max. 225 (102)	Max. 250 (113)
Weight of heaviest part (w/o battery, baskets and seat)	lb (kg)	44 (20)	53 (24)	25 (11)	40 (18)
Total Weight (w/ batteries, basket, seat)	lb (kg)	79 (36)	89 (41)	82 (37)	130 (59)
Each Battery Module Weight	lb (kg)	22 (10)	18 (8)	22 (10)	20 (9)
Battery Module Capacity	$\frac{V}{x}$ Ah Pcs	12V12Ah x 2	12V12Ah x 2	12V12Ah x 2	12V12Ah x 2
Charger		Off Board (2A)	Off Board (2A)	Off Board (2A)	Off Board (2A)
Output Power of Motor	hp (W)	0.47 (350)	0.45 (336)	0.75 (559)	0.75 (559)
Maximum Speed ²	mph (km/hr)	3.75 (6)	3.75 (6)	3.50 (6)	5 (8)
Maximum Climbing Angle (based on user weight of 90kg/200lb) /Safe Climbing Angle	% (°)	10 (6)/17 (10)	10 (6)/17 (10)	14 (8)	14 (8)
Range ³ (per charge w/ STD 12AH Battery / 90 kg User Weight) (After the battery and mechanical moving parts fully break in)	mile (km)	11 (18)	10 (16)	10 (16)	10 (16)
Turning Radius	in (mm)	39 (1000)	46 (1160)	40 (1015)	40 (1015)
Ground Clearance	in (mm)			2	3
Handle Bar	Type	T	T	T	T

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

1. Include the Anti-Tip wheel.
2. Driver weight may exceed weight of the unit; speed must be reduced when turning.
3. The actual driving range varies with the factors shown below:
 - a) the weight of occupant
 - b) ground surface
 - c) battery conditions
 - d) type of charger
 - e) ambient temperature
 - f) the way of driving
 - g) etc.

QUARTERLY INSPECTION

For your own safety, quarterly inspection and service on the product has to be performed and signed by an authorized dealer. Maintenance records (below) should be kept at all times. The manufacturer / distributor / vendor will be indemnified from any product liability claim if the above maintenance / service requirement is not met.

NOTE! Regular (Monthly) inspection is strongly recommended by the manufacturer to ensure ultimate performance of the vehicle.

Service Record:

Date of Purchase: / /

Purchaser: _____ **Model #:** _____ **Serial #:** _____

Dealer Unit Was Purchased From: _____

M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y
M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y
M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y
M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y
M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y	M / D / Y

WARRANTY

Please refer to warranty information included with unit.

Serial No.

DISCLAIMER

Congratulations on your purchase of the *Shoprider*®

It is not intended to be used by individuals with physical limitations that could prevent the user from operating this unit safely. *Shoprider*® disclaims all responsibility for any personal injury or property damage, which may occur as a result of improper or unsafe use of its products. Mechanical or electrical defects will be dealt with on a contingency liability basis.

The preceding guidelines are intended to assist you in the safe operation of your powered scooter. If you should have any questions about the correct operation of your scooter, please contact your authorized *Shoprider*® dealer.

Model No.

Serial No.

Dealer's Stamp

Shoprider® Mobility Products, Inc.
(800) 743-0772
www.shoprider.com

Notes